

The excellent appearance in accord with ergonomic design

Integrated body design makes products maintains long-term stability.

High quality 3W LED lamp and long usage life.

Head: Binocular Head, Sidentoph at 30°, 360° Rotatable, Interpupillary Distance 50-75 mm, Diopter Adjustable ± 5 On Left Tube

Eyepiece: Wide Field Eyepiece WF 10X/20mm

Objective: SP Plan Achromatic Objectives 4x, 10x, 40x,

100x(oil)

Viewing Head: Articulated Free Trinocular Head, 30°inclined,

Interpupillary Distance 50-75mm

Nosepiece: Reverse Quadruple Nosepiece (inward facing) **Focusing System:** Coaxial Coarse and Fine Adjustments,

Fine Division 0.002mm, Coarse Stroke 37.7mm Supplied With

An Adjustable Rack Stop To Prevent Damage To Sample And

Objectives, The Coarse Adjustment Are Equipped With

Friction Control

Stage: Double Layer Mechanical Stage 140x140mm,

Moving Range 50x75mm

Illumination: 3W LED, Brightness

Adjustable, Powered by 110-240V Adapter

Packaging: Inner Thermocol/Styrofoam Packing and Outer Cardboard Box.

RESEARCH BINOCULAR MICROSCOPE **FXL-Bino**















